



CF-100 SERIE ACTIVATED CARBON FILTERS TECHNICAL SPECIFICATIONS

Model	Flowrate m3/h				Mineral quantity (lt)	Tank Dimensions		Connection
	Min.	Avg.	Max.	Backwash		DxH (cm)	D"xH"	
Activated Carbon Filters: Granular Activated Carbon Media (Taste, colour, smell, organics, free chlorine removal)								
CF 20/P8-56	0,3	0,6	0,9	0,9	20	20x89	8x17	1"
CF 30/P10-56	0,5	1,0	1,5	1,5	30	25x89	10x35	1"
CF 50/P10-56	0,5	1,0	1,5	1,5	50	25x137	10x54	1"
CF 75/P13-77	0,9	1,7	2,6	2,6	75	33x137	13x54	1"
CF 100/P14-77	1,0	1,9	2,9	2,9	100	35x165	14x65	1"
CF 125/P16-77	1,3	2,5	3,8	3,8	125	40x165	16x65	1"
CF 150/P18-77	1,6	3,2	4,8	4,8	150	45x165	18x65	1"
CF 200/P21-77	2,2	4,4	6,6	6,6	200	53x153	21x62	1"
CF 300/P24-28	2,9	5,8	8,8	8,8	300	61x175	24x72	1"1/2
CF 450/P30-29	4,5	9,1	13,6	13,6	450	76x183	30x72	2"
CF 600/P36-31	6,5	13,0	19,5	19,5	600	91x183	36x72	2"
CF 800/P42-31	8,8	17,6	26,5	26,5	800	106x198	42x72	2"