

ROTAPUR 100 serie reverse osmosis units are designed for commercial use. The product is very easy to assemble and can be mounted in tight spaces thanks to its compact structure.

Point of Use

- ◆ Drinking water
- ◆ Coffee, tea machines
- ◆ Fruit and vegetable washing
- ◆ Ice machines



R-104 RO unit

Standard Features

- ◆ TFC spiral wound membrane elements
- ◆ 220 V / 1 phase / 50 Hz power supply
- ◆ Pump
- ◆ 20 "5 μ filter
- ◆ 20 "Pre-carbon filter
- ◆ 20 "1 μ filter
- ◆ RO membrane elements
- ◆ Post carbon filter
- ◆ 11 Galon reserve tank



TDS meter

OPERATING CONDITIONS	
Feed water pressure	2 – 6 bar
Max feed water TDS	500 mg/l
Feed water temperature	5 - 40 °C
Recovery	%20

ROTAPUR 100 SERIE TECHNICAL SPECIFICATIONS				
Model	Flowrate lt/day	RO Membrane Qty (no)	Recovery %	Dimension L x H x W (cm)
R 102	500	2	20	48 x 75 x 25 + 55xØ38 cm
R 103	900	3	20	48 x 75 x 25 + 55xØ38 cm
R 104	1200	4	20	48 x 75 x 25 + 55xØ38 cm
R 105	1500	5	20	48 x 75 x 25 + 55xØ38 cm

1. If there is a change in the feed water temperature, pressure and TDS, there may be changes in water production.
2. The device should not be used if the input water quality and microbiological condition are not known.